



modular air-conditioners & heat pumps










Enviromax´ CLIMATE CONT

SINGLE PHASE POWER

- Position Internally
 - FREE BLOWING
- Position Externally
 - DUCT UP TO 20 METRES
- Trouble Free Operation
 - PUMPED CONDENSATE









Get In Touch

Call: 0845 6880112



Email: info@adremit.co.uk

Our Address

___10





modular air-conditioners & heat pumps











The Environmax 10's flexible design has been proven over 5 years of operational experience, specifically developed for efficient installation, internally or externally and requiring only single phase power. The units also utilise copeland scroll compressor technology. with 40 years of manufacturing history.

Specification

Height: 1465mm Length: Width: Weight: 175Kgs

Handling: Fork pockets and easy move castors

Sound Level: 52 dba @ 5 metres Supply Air Flow: 1,450 Cubic m/hour

Configuration-

Supply Air: Free blow via grill or 2 x 300mm

diameter ducts (20m max)

Condenser Air: 2 x 300mm diameter ducts (5m max)

Controller-Unit mounted or optional 24 Volt remote

> controller/thermostat. Unit is supplied with integral controller for AirCon, Heating and

basic DeHumidification operation.

Performance

10+kW Air-Conditioning capacity*



180 ltrs /24hrs Dehumidification

Specifications are based on Environax standard test conditions. Nominal' operating condition is 12 to 30°C db ambient operating temperature range, with a 240V/50HZ power supply (output capacity will vary in relation to operating wet bulb temperature and Relative Humidity conditions, higher ambient conditions will increase the running

Optional internal thermostat and controls give ease of operation



Easy handling with integral fork pockets and robust frame



Unit fits through a standard doorway on easy move castors



enviromax **CLIMATE SOLUTIONS**



Get In Touch

Call: 0845 6880112

Email: info@adremit.co.uk

Our Address