

# PA3525WH IPX4 AIR CURTAIN

Item no. 26398

Document type: **Product card**  
 Document date: **2019-07-03**  
 Generated by: **Systemair Online Catalogue**

## Description

### Stylish air curtain for commercial premises, with intelligent control

- Horizontal mounting
- Installation height up to 3,5 metres\*
- Vertical mounting
- Installation width up to 5 metres\*  
(2 units), one on each side

### Application

Air curtain PA3500 gives more possibilities than ever before, packed into the same product. There are therefore many areas of use. PA3500 is particularly suitable for entrances to stores and shopping centres for example.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

### Design

Through its timeless design and its many accessories, it's easy to get PA3500 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.

## Technical parameters

Unit	
Type of installation	Horizontal/Vertical
Type of heating	Water heat
Length	2549 mm
Height	306 mm
Depth	525 mm
Weight	92 kg
Max. installation height	3500 mm
Color casing	RAL 9016, NCS S 0500-N
Color, outlet grilles	RAL 7046
Protection class	IPX4
Ambient working temperature range (dry conditions)	-20-30 °C
Air flow	
Air flow step 5	5100 m³/h
Air flow step 4	4500 m³/h
Air flow step 3	3750 m³/h
Air flow step 2	3050 m³/h
Air flow step 1	2300 m³/h

Sound data		
Sound power level LWA	79	dB(A)
Sound level step 5	63	dB(A)
Sound level step 4	61	dB(A)
Sound level step 3	57	dB(A)
Sound level step 2	52	dB(A)
Sound level step 1	46	dB(A)
Control/motor data		
Control/motor supply	230	V
Phase	1	~
Control/motor current, 50Hz	5,7	A
Control/motor current, 60Hz	7	A
Motor power 50Hz	1310	W
Motor power 60Hz	1570	W
Heater		
Max. water temperature	110	°C
Max. working pressure	16	bar
Dimension water connections	DN20	
Water content in coil	2,9	l
Water heating full output 80/60 °C, air +18 °C	29,3	kW
Pressure drop water 80/60 °C, air +18 °C	9	kPa

## Accessories









### Electric accessories

- [SIREDC Door contact \(17495\)](#)
- [SIRERTX Room sensor \(17539\)](#)
- [SIRECC603 3m Modular cable \(17542\)](#)
- [SIRECC605 5m Modular cable \(17543\)](#)
- [SIRECC615 15m Modular cable \(17545\)](#)
- [SIRECC640 40m RJ12 on. cable \(17773\)](#)
- [SIREACY Competent kit \(33488\)](#)
- [SIREAAY Advanced kit \(33490\)](#)
- [SIREBN Basic kit \(33481\)](#)
- [SIREACZ Competent kit \(33489\)](#)
- [SIREAAZ Advanced kit \(33491\)](#)

## Accessories

[SIREWTA Sensor \(17613\)](#)  
[VOSP15LF valve kit \(17522\)](#)  
[VOSP15NF valve kit \(17523\)](#)  
[PA34EF25 External inlet filter \(19067\)](#)  
[PA3XT25 Outlet extension \(19088\)](#)  
[PA34VD30 Vibration damper \(18067\)](#)  
[PA3DW25 Design kit wall \(110837\)](#)  
[PA3JK Vertical kit/Joining kit \(110759\)](#)  
[PA34WB30 Wall brackets \(18046\)](#)  
[PA34WS30 Wire suspension \(18064\)](#)  
[PA3VDW25 Design kit vertical \(110753\)](#)  
[PA34TR30 Threaded Rods \(18058\)](#)  
[PA34CB30 Ceiling Bracket \(18061\)](#)  
[SD230 Actuator 230V \(16979\)](#)  
[ST23024 Transformer for 24V \(16981\)](#)  
[DTV200S Filterguard 20-300 Pa \(17597\)](#)  
[VLP15LF Valve system \(79375\)](#)  
[VLP15NF Valve system \(79376\)](#)  
[VLP20 Valve system \(79377\)](#)  
[VLP25 Valve system \(79378\)](#)  
[VLSP15LF Valve system \(79379\)](#)  
[VLSP15NF Valve system \(79380\)](#)  
[VLSP20 Valve system \(79381\)](#)  
[VLSP25 Valve system \(79382\)](#)  
[VLP32 Valve system \(79416\)](#)  
[VLSP32 Valve system \(79417\)](#)  
[SDM24 Actuator 24V \(16977\)](#)

## Documentation

-  [ma\\_frico\\_pa3500-4200\\_gb\\_180926.pdf \(3,49MB\)](#)
-  [ma\\_frico\\_PA3JK\\_PA4JK\\_PA34VDW\\_vertical.pdf \(1,53MB\)](#)
-  [ma\\_frico\\_PA3XT\\_PA4XT\\_150415.pdf \(381,55kB\)](#)
-  [ma\\_frico\\_pa34tr\\_pa34cb-pa34vd.pdf \(739,11kB\)](#)
-  [ma\\_frico\\_pa34ws\\_pa34cb.pdf \(916,13kB\)](#)
-  [ma\\_pa34jk\\_pa34dw\\_horizontal.pdf \(1,74MB\)](#)
- 
-  [cat\\_frico\\_pa3500\\_pa4200\\_gb.pdf \(1,43MB\)](#)
-  [cat\\_frico\\_ac\\_sire\\_valves\\_gb\\_20170523.pdf \(345,98kB\)](#)
- 
-  [wd\\_frico\\_pa3500\\_gb.pdf \(168,30kB\)](#)
- 
-  [DoC Air curtains\\_gb 2017-04.pdf \(224,51kB\)](#)
- 
-  [pa3525w-2D\\_1.dwg \(222,03kB\)](#)
-  [pa3525w-3D\\_1.dwg \(384,93kB\)](#)

## Specification text

### **Stylish air curtain for commercial premises, with intelligent control**

- Horizontal mounting
- Installation height up to 3,5 metres\*
- Vertical mounting
- Installation width up to 5 metres\*  
(2 units), one on each side

#### **Application**

Air curtain PA3500 gives more possibilities than ever before, packed into the same product. There are therefore many areas of use. PA3500 is particularly suitable for entrances to stores and shopping centres for example.

The air curtain has many intelligent and energy saving features which provide fully automatic protection for the entrance, adaptable to each area of use.

#### **Design**

Through its timeless design and its many accessories, it's easy to get PA3500 to blend well into the premises. Front and service hatch can be finished in any colour to perfectly match the environment. The air curtain is available for horizontal, vertical and recessed installation.

\*) Recommended installation height and width varies depending on the relevant premises.